





Specifications

Product Name: NITSOL UPS

Capacity: 600 VA

Type: DSP Pure Sine Wave

Backup: 2.5 Hrs.

Input Voltage: 140V-280VAC

Input Frequency: 50 Hz

Power Factor: 0.7 (Full Load)

Output Voltage: 220V
Output Frequency: 50Hz
Battery Voltage: 12V

Battery Capacity: 100 AH

Battery Type: LiFePO4 Battery Pack

Charging Current: 1-15AMP
Charging Cut Off: 17 V

Operating Temp: 0- 45°C

Protection: Input Volt High /Low, Battery Deep Discharge, Battery Over Charge, Over Temperature, Short Circuit, Return Voltage, Over Load, Battery Terminal Open.

LCD Display Parameters:

Input Mains Voltage

Output Voltage

Output Frequency

Battery Status

Charging Current

Charging Status

Load Status

Low Battery Alarm and Trip

Over Load Alarm and Trip

Short Circuit Trip

Over Temperature Trip Battery Terminal Open.

Level 3, H#41, R#07, Block#G

Banani, Dhaka-1213

Web: www.nitsolbd.com Email: info@nitsolbd.com

Phone/Whatsapp: +8801746744929

NITSOL IPS & Lithium ION Battery

Watt 400 W Load capacity, 3 LED/CFL Light (20W) + 2 Fan (80W) + 1 LED/LCD 24" TV (100W) + 1PC + 4 Mobile Charger (5W) Back Up Time 2.5 Hrs, LiFePO4 Battery Pack 12V 100AH Battery Qty 1 pcs With VMS (Voltage Management System)

- * Low Charging Time (Approximately 4 Hours for Full charge, whereas conventional Lead Acid Batteries require 9-10 Hours)
- * Maintenance Free Long-Life Battery
- →Long Backup (High Discharge Capacity)
- * Durable with support on fingertips
- * Heavy Load Capacity
- * Transformer Based UPS which is durable and Long-lasting
- * Internal temperature-based cooling system for battery unit which is reliable and safe.

Limited Time Offer
Battery 5 Years warranty
UPS 2 Years Warranty
Please Call for Price

Rakib: +8801746-744929

Saurov: +8801712494860